

ISIFLO Support Liner



Isiflo Support Liner is used on SDR11 and SDR17 PE-pipes according to EN-12201 and EN-1555-2 to straighten out ovality and add structural support in the interface between pipe end and fitting. The pressure loss using this liner is minimal. For gas pipes Isiflo Support Liner should always be used.

Visit www.isiflo.com for more details.

1. Product Description

Materials	PA12/GF
Dimension	20-63 mm
Max working pressure	16 bar
Temperature range	Up to +40°C
Medium	Water (16 bar), Air (10bar), gas, petrol, diesel, glycol and ethanol. Other medium; contact Isiflo for details.
Approvals	Kiwa Gastec
Surface treatment	None
Color	Black
Other information	Can be buried.

2. Description of use and Maintenance

Cleaning

Can be cleaned with mild soap water. Use a clean and dampened cloth.

Inspection and control

Check for leakage.

Maintenance instruction and intervals

No maintenance necessary.

3. Operation Technical Information

Estimated technical lifetime without replacements:

>50 years.

Warranty and conditions:

20 years against fabrication errors.

Moisture resistance:

Not affected by moisture.

Easiness of cleaning:

Good.

Other information:

To be recycled as general waste at end of life.

Product details and instructions for use:

www.isiflo.com

4. Contact

Producer/manufacturer	Isiflo AS
Address	Box 143
Postcode and city	2831 Raufoss
Phone	(+47) 61152700
E-mail	info@isiflo.com
Web	www.isiflo.com